

CERTIFIED PLASTIC ANCHOR Ø 10



Code	Commercial Description	Dimensions	Conf.	Pallet	Selling Unit
TERII-2213	Maximum anchoring 20 - 30	60 mm	250	32000	PZ
TERII-2214	Maximum anchoring 30 - 40	70 mm	250	32000	PZ
TERII-2216	Maximum anchoring 40 - 60	90 mm	250	24000	PZ
TERII-2218	Maximum anchoring 70 - 80	110 mm	250	16000	PZ
TERII-2220	Maximum anchoring 90 - 100	130 mm	250	16000	PZ
TERII-2223	Maximum anchoring 100 - 120	150 mm	250	11250	PZ

TERII-2224	Maximum anchoring 120 - 150	180 mm	250	11250	PZ
TERII-2225	Maximum anchoring 150 - 180	210 mm	250	8750	PZ
TERII-2226	Maximum anchoring 180 - 210	240 mm	250	8750	PZ
TERII-2220B		ø 10 L 130	100	16000	0
TERII-2216BB		ø 10 L 90	100	16000	0

Description

Hammering anchor hole 8 mm, with head from 60 mm and steel expansion nail with coloured cap. It complies to ETAG014 and it complies also with the certificate ETA04-0030.

Material

Made of PP (polypropylene), steel nail.

Use

Utilized for the mechanical anchoring of the insulating panels almost all types of masonry, supporting the load and the tensile stress "tear off".

