

PVC-ALUMINIUM AND COPPER UNDER-RIDGE



| Code | Commercial Description | Dimensions | Conf. | Pallet | Selling Unit |
|--------------|--|--------------|-------|--------|--------------|
| LUC70-9070A | Pvc-Aluminium red under-ridge | 390 mm x 5 m | 0 | 72 | PZ |
| LUC70-9070AN | Pvc-Aluminium black under-ridge. Upon request only | 390 mm x 5 m | 0 | 72 | PZ |
| LUC70-9070R | PVC Undercollar Copper Terracotta | 360 mm x 5 m | 0 | 72 | PZ |
| LUC70-9070RM | | 360 mm x 5 m | 4 | 72 | 0 |
| LUC70-9070RN | | 360 mm x 5 m | 4 | 72 | 0 |

Description

Roof under-ridge in rolls, central part in PVC, heat-sealed to the "flashings on the sides made of aluminum or copper. PVC ensures an excellent resistance to heat and UV rays. Butyl strips on the intrados of the flashings element in aluminum or copper, makes the installation easier and ensures better adherence to the brick. Resistant to temperatures from -40 ° C to 150 ° C.

Material

Manufactured in PVC with aluminium/copper pleating.

Use

Used to facilitate ventilation of the roof ridge.