

ANCHORS SGR-AP



Code	Commercial Description	Dimensions	Conf.	Pallet	Selling Unit
TER11-3110AP	Anchor SGR-AP - 110 mm	110 mm	100	9000	PZ
TER11-3130AP	Anchor SGR-AP - 130 mm	130 mm	100	9000	PZ
TER11-3150AP	Anchor SGR-AP - 150 mm	150 mm	100	9000	PZ
TER11-3170AP	Anchor SGR-AP - 170 mm	170 mm	100	7200	PZ
TER11-3190AP	Anchor SGR-AP - 190 mm	190 mm	100	7200	PZ
TER11-3210AP	Anchor SGR-AP - 210 mm	210 mm	100	5400	PZ

TER11-3230AP	Anchor SGR-AP - 230 mm	230 mm	100	5400	PZ
TER11-3250AP	Anchor SGR-AP - 250 mm	250 mm	100	5400	PZ
TER11-3270AP	Anchor SGR-AP - 270 MM	270 mm	100	5400	PZ
TER11-3290AP	Anchor SGR-AP - 290 MM	290 mm	100	4500	PZ
TER11-3310AP	Anchor SGR-AP - 310 MM	310 mm	100	4500	PZ

Description

Hammering anchor hole 8 mm, with pre-assembled nail into the anchors body.Dimension of the head 60 mm with improved adherence and torx-ready coloured plastic nail cap.It complies to EAD 330196-01-0604.Main features of this product: Pre-assembled nail, for a faster installation. Variable section of the anchors body (fixing diameter 8 mm). Asymmetric expansion of the anchors body. Customizable anchors head. Packed in box of 100 pcs. each.

Material

Barrel and ferrule made of PP (polypropylene), steel nail and PA (polyamide) nail cap.

Use

Used for the mechanical anchoring of insulating panels, mineral wool and for the main types of masonry, supporting its load and tensile stress.The pre-assembled nail facilitates and accelerates the installation of the anchor.

