

THERMAL INSULATING SELF-EXTINGUISHING ANCHORS SGR-PA



Code	Commercial Description	Dimensions	Conf.	Pallet	Selling Unit
TER11-3110AUT	Class V0 self-extinguishing plugs for coatings - p...	110 mm ø 8 mm	100	9000	0
TER11-3130AUT	Class V0 self-extinguishing plugs for coatings - p...	130 mm ø 8 mm	100	9000	0
TER11-3150AUT	Class V0 self-extinguishing plugs for coatings - p...	150 mm ø 8 mm	100	9000	PZ
TER11-3170AUT	Class V0 self-extinguishing plugs for coatings - p...	170 mm ø 8 mm	100	7200	PZ
TER11-3190AUT	Class V0 self-extinguishing plugs for coatings - p...	190 mm ø 8 mm	100	7200	0
TER11-3210AUT	Class V0 self-extinguishing plugs for coatings - p...	210 mm ø 8 mm	100	5400	0
TER11-3230AUT	Class V0 self-extinguishing plugs for coatings - p...	230 mm ø 8 mm	100	5400	0
TER11-3250AUT	Class V0 self-extinguishing plugs for coatings - p...	250 mm ø 8 mm	100	5400	0

Description

Class V0 indicates that the pre-assembled polyamide nail fastener has the ability to stop the spread of fire within the first 10 seconds of exposure to flames. This means that in the event of a fire, the fixing will prevent the spread of flames through the thermal insulation panels. Fire-retardant V0 class thermal coat fixings are an essential component to ensure fire safety in the building. Using these fixings during the installation of the thermal coat can limit the damage to the building and safeguard the lives of people inside in case of fire.

Material

Plastic material in VO class.

Use

Used for mechanical anchoring of mineral wool insulation panels, as well as the main types of masonry, supporting the load and tensile stress "tear".

