

THERMAL INSULATING SELF-EXTINGUISHING ANCHORS SGR-AV



Code	Commercial Description	Dimensions	Conf.	Pallet	Selling Unit
TER11-3110AVAUT	Class V0 self-extinguishing plugs for coatings - p...	110 mm ø 8 mm	100	9000	0
TER11-3130AVAUT	Class V0 self-extinguishing plugs for coatings - p...	130 mm ø 8 mm	100	9000	0
TER11-3150AVAUT	Class V0 self-extinguishing plugs for coatings - p...	150 mm ø 8 mm	100	9000	0
TER11-3170AVAUT	Class V0 self-extinguishing plugs for coatings - p...	170 mm ø 8 mm	100	7200	PZ
TER11-3190AVAUT	Class V0 self-extinguishing plugs for coatings - p...	190 mm ø 8 mm	100	7200	0
TER11-3210AVAUT	Class V0 self-extinguishing plugs for coatings - p...	210 mm ø 8 mm	100	5400	0

TER11-3230AVAUT	Class V0 self-extinguishing plugs for coatings - p...	230 mm ø 8 mm	100	5400	0
TER11-3250AVAUT	Class V0 self-extinguishing plugs for coatings - p...	250 mm ø 8 mm	100	5400	0
TER11-3270AVAUT	Class V0 self-extinguishing plugs for coatings - p...	270 mm ø 8 mm	100	5400	0
TER11-3290AVAUT	Class V0 self-extinguishing plugs for coatings - p...	290 mm ø 8 mm	100	4500	0
TER11-3310AVAUT	Class V0 self-extinguishing plugs for coatings - p...	310 mm ø 8 mm	100	4500	0

Description

Class V0 indicates that the pre-assembled galvanised steel screw fastener has the ability to stop the spread of fire within the first 10 seconds of exposure to flames. This means that in the event of a fire, the fastener will prevent the spread of flames through the thermal insulation panels. Fire-retardant V0 class thermal coat fixings are an essential component to ensure fire safety in the building. Using these fixings during the installation of the thermal coat can limit the damage to the building and safeguard the lives of people inside in case of fire.

Material

Plastic material in V0 class.

Use

Used for mechanical anchoring of mineral wool insulation panels, as well as the main types of masonry, supporting the load and tensile stress "tear".

